

OLS 4.8 Pro

ICONIC
outdoor

CABINET
OL SERIES



Ultra-Wide Viewing

140° horizontal.
120° vertical.

which can maximize the coverage of the audience and improve the return on investment

Ultra-High Refresh Rate

3.840Hz

no trailing, no frame flickering even when playing fast-moving contents

Outdoor fixed ICONIC LED Displays are available with various pixel pitch using DIP & SMD lamps. Provide solutions for any weather conditions in high resolution images with the great brightness and contrast levels. It results the perfect picture every time, even under direct sunlight. Iconic Outdoor Series are perfectly designed for outdoor signage application with various pixel pitch. The LED cabinet is designed with an easy installation and fast module maintenance up to 3 times efficiency within 30 seconds.

Specification

Pixel Pitch	4.8mm
Pixel Density	43.402dots/m ²
LED Configuration	SMD 2727
Module Size	250 x 250 (W x H)
Module Resolution	52 x 52
Contrast Ratio	5.000 : 1
Cabinet Size	1.000 x 1.000 mm (W x H)
Cabinet Resolution	208 x 208
Cabinet Weight	Aluminum/Iron : 45/55kgs
Maintenance Type	Rear Maintenance
IP Rating	IP65/55

Brightness	5.000nits
Viewing Angle	140°, 120° (H,V)
Driving Type	1/13
Grayscale	14bit
Max/Avg Power Consumption	800/240 W/m ²
Voltage	AC 110~240V
Frequency	50/60Hz
Refresh Rate	3.840hz
Lifetime	100.000hours
Operating Temperature	-20°C ~ 65°C
Operating Humidity	10% ~ 90%